

# Floor Cleaners

**15k or 20k psi and a 24" Jet Path**



## FCSV Floor Cleaner



Available with or without vacuum system.

## FC-TRI Floor Cleaner 3 Wheel Model



Excellent maneuverability and a simple height adjustment.

The **FCSV**, **FC-TRI** and **FCSG** are self-rotating, manual powered floor cleaners and surface prep machines, operating at 15k or 20k psi. The differences between the three models are that the **FCSV** comes with a 4" Camlock vacuum system while the **FCSG** and the **FC-TRI** do not.

## Easy and Safe Operation

Now you can clean garages, parking lots and other flat surfaces safely and effectively while eliminating operator hazard. It also cleans paint from gratings, decontaminates and degreases surfaces, removes coatings and membranes, scarifies concrete and cleans tank and pit floors.

## 4 Jet Arms Free Spinning

These tools are made of corrosion resistant zinc plated steel and come with a **StoneAge® SG-30** free spinning swivel connected to four jet arms. The swivel operates at 300-1,000 rpm from the jet reaction and uses **AP4 Attack® Tips**.



Radiused arms for quality jets.

An optional vacuum attachment allows waste and debris to be removed through a standard 4" Camlock vacuum hose connection. A hand operated dump valve discharges the water pressure, shown in the photo at right.



Easy to hold dump lever.

## FCSV & FCSG Specifications

MODEL	MAX. PRESS	FLOW	JET PATH	HEIGHT RANGE	WEIGHT
<b>FCSV &amp; FCSG</b>	15k or 20k psi	28 gpm	24 in	1-5 in	255 lbs
	1000 or 1400 bar	110 lpm	61 cm	3-13 cm	116 kg
<b>FC-TRI</b>	15k or 20k psi	28 gpm	24 in	1-3.5 in	341 lbs
	1000 or 1400 bar	110 lpm	61 cm	3-9 cm	155 kg

www.stoneagetools.com • www.sewernozzles.com  
 Phone Orders: 970-259-2869 • Fax Orders: 970-259-2868  
 email orders: sales@stoneagetools.com

