

Deck Blaster

Up to 40k psi and a 14" Jet Path



SURFACE PREP

Upgraded for 2007

8-Jet Bar Head

The Bar Head manifold allows up to 8 nozzles to be used at a time. Maximum jet path is 14".



Convenient Controls

The dump valve and rotation are controlled by lifting the lever and the forward speed is activated by a pull of the knob.

Height Adjustment

A simple adjustment allows the height to be changed quickly and easily.

40k psi Dump Valve*

Two options available.

Vacuum Recovery

A 3" vacuum attachment can pivot to either side for easy clean up.

Self Propelled Drive

The **Deck Blaster** uses air-powered speed adjustments to let you maximize your efficiency and production time.

Rotation Control

The rotation speed is independently controlled and is adjustable via a valve. It operates at 250-1,000 rpm.

Spray Skirt

Deck Blaster Specifications

MODEL	MAX. PRESS	FLOW	JET PATH	SPEED RANGE	WEIGHT	NOZZLE
DB-XX	40k psi	6 gpm	14 in	3 - 20 ft/min	215 lbs	OS6
	2800 bar	23 lpm	35 cm	.9 - 6.0 m/min	116 kg	OS6

* -XX We offer this unit with your choice of either Jetstream or Gardner Denver dump valve.



www.stoneagetools.com • www.sewernozzles.com
 Phone Orders: 970-259-2869 • Fax Orders: 970-259-2868
 email orders: sales@stoneagetools.com