

SH & SL Swivels

Connecting Your Hose for Twist Free Operations



**Don't fight
hose twist!
The SH Hose
Swivel eases
hose handling.**

SH Swivel Here —————

SH Swivel Specs	
MODEL	SH-P8P8
Max. Pressure	15k psi 1000 bar
Max. Rotation Spd	250 rpm
Flow Capacity	50 gpm 190 lpm
Flow Rating	2.3
Inlet Port	1/2 npt
Shaft Connection	1/2 npt
Overall Length	4.125 in 10.5 cm
Weight	1.9 lb .9 kg
Body Diameter	2.25 in 57 mm



SL-P8P4-0°

SL-M9AV9-0°

SL-H9H9-C

Each of our **SL Swivels** is offered with optional 90° inlet nuts, replaceable seals, smooth ball bearings, stainless steel construction and low torque for easy rotation.

SL Swivel Series Specifications						
MODEL	SL-P8P4		SL-M9AV9		SL-H9H9-C	
Max. Pressure	15k psi	1000 bar	20k psi	1400 bar	40k psi	2800 bar
Max. Rotation Spd	1000 rpm		800 rpm		2000 rpm	
Flow Capacity	35 gpm	130 lpm	25 gpm	95 lpm	10 gpm	38 lpm
Flow Rating, Cv	1.6		1.1		.30	
Inlet Port	1/2 npt 0° or 90°		9/16 MP 0° or 90°		9/16 HP 0°	
Shaft Connection	1/4 npt		9/16 MP		9/16 HP	
Overall Length	4.6 in	12 cm	5.9 in	13 cm	5.9 in	13 cm
Weight	1.63 lb	.74 kg	2.0 lb	.89 kg	2.0 lb	.89 kg
Body Diameter	1.75 in	45 mm	1.75 in	45 mm	1.75 in	45 mm

www.stoneagetools.com • www.sewernozzles.com
 Phone Orders: 970-259-2869 • Fax Orders: 970-259-2868
 email orders: sales@stoneagetools.com



© Jan '07