

WT & WS - Small Pipes

For Cart Jettors & Trailer Jettors



WT & WS WARTHOGS®: Small and Mighty!

These small **WARTHOG**® sewer models have all the powerful features of the larger tools, but they can negotiate elbows and cleanouts commonly found in laterals from homes, buildings, restaurants, and other light commercial facilities.



WT-3/8
3" - 6" Lines

US Patent 5,964,414

The **WT-3/8** is designed specifically to handle 3" - 6" lines and cleanouts. This tool is most commonly used on small capacity pumps and cart jettors.

WS-1/2
4" - 8" Lines

US Patent 5,964,414

The **WS-1/2** is designed to handle 4" - 8" lines and is most commonly used with trailer jettors. This tool is a real workhorse and really delivers.

SEWER JETTING

WARTHOG® WT & WS Specifications

MODEL	WT-3/8		WS-1/2	
Maximum Pressure	4,000 psi	275 bar	4,000 psi	275 bar
Operating Pressure	1,500 - 4,000 psi	100-275 bar	1,500 - 4,000 psi	100-275 bar
Rotation Speed	300-500 rpm		200-500 rpm	
Flow	5-12 gpm	20-40 lpm	8-20 gpm	30-70 lpm
Flow Rating	0.75 Cv		1.3 Cv	
Pulling Force	5-20 lbs	22-89 nt	9-27 lbs	40-120 nt
Inlet Port	3/8 npt		1/2 npt	
Tool Diameter	1.9 in.	48 mm	1.8 in.	44 mm
Length	3.0 in.	76 mm	4.4 in.	112 mm
Ports	3 x 1/8 npt		3 x 1/8 npt	
Weight Complete	1.2 lb	.54 kg	2.95 lb	1.33 kg



Both the **WT** and **WS** models negotiate elbows effortlessly. They are designed for cart and trailer jettors.