

Ferret Nozzles

15k psi Power for 1.1"- 2" Tubes



The Ferret has similar power as the **Marten** but is designed for smaller tubes, from 1.1"-2" diameters.



Ferret Tube Nozzle

Effective Rotation, Controlled Jetting

Both the **Marten** and **Ferret** offer Polisher and Unplugger head configurations. These tools are powerful enough to cut holes in sandstone, as shown in the photo top right. Note the jetting charts below with pressure and flow options.

US Patent 5,964,414

**FT 042
Polisher Head**

Specifically designed to aggressively clean the inner walls of tubes.

- 3 jets @ 85°
- 3 jets @ 105°



**FT 043
Unplugger Head**

Your best choice for clearing plugged tubes.

- 1 jet @ 15°, 30°, 45°
- 2 jets @ 135°



TUBE CLEANING

Ferret Specs	
Model	Ferret
For Tubes I.D.	1.1"-2" 29-51mm
Max Pressure	15k psi 1000 bar
Flow Capacity	12 gpm 45 lpm
Flow Rating	0.4 Cv
Rotation Speed	1000 rpm
Inlet Port	1/4 npt
Body Diameter	0.91 in 23 mm
Weight	1.0 lbs 0.45 kg
Length Overall	6.75 in 171 mm

Polisher Jetting	
Model	FT 042
Pressure	Flow
10k psi 700 bar	12 gpm 45 lpm
15k psi 1000 bar	12 gpm 45 lpm

Unplugger Jetting	
Model	FT 043
Pressure	Flow
10k psi 700 bar	10 gpm 35 lpm
10k psi 700 bar	12 gpm 45 lpm
15k psi 1000 bar	10 gpm 35 lpm
15k psi 1000 bar	12 gpm 45 lpm



www.stoneagetools.com • www.sewernozzles.com
 1-866-795-1586 (Toll Free in the U.S) or 970-259-2869 • Fax: 970-259-2868
 email: sales@stoneagetools.com