

# Extension Nipples

**Put Your Nozzle Tips Close to the Work**



## Precision-machined Stainless Steel Nipples

Maximize jet power and removal rates by getting your jets close to the target surface. Extension nipples also improve jet quality for longer throw and harder hitting.

- Durable stainless steel construction
- Sizes in stock for all StoneAge® tools
- Makes smaller pumps capable of bigger jobs



### SA 567-P4P2

Fits 1/4 npt ports  
AP2 Attack Tips  
15k psi

### SA 356-P8P4

Fits 1/2 npt ports  
AP4 Attack Tips  
15k psi

### SA 577-G12P4

Fits G12 ports  
AP4 Attack Tips  
20k psi

### SA 569-G9S6

Fits G9 ports  
OS6 Sapphire Tips  
40k psi

## Nipple Extension Specifications

DESCRIPTION	PART #	MAWP	THREADS	OD	ID
9/16 MPTubing	<b>SA 567-P4P2*</b>	15k psi 1000 bar	1/2 npt, 1/8 nptf	.563 in. 14.3 mm	.312 in. 7.9 mm
9/16 MPTubing	<b>SA 567-M9P2</b>	20k psi 1400 bar	9/16 MP, 1/8 npt	.563 in. 14.3 mm	.312 in. 7.9 mm
9/16 MPTubing	<b>SA 567-M9M9</b>	20k psi 1400 bar	9/16 MP, 9/16 MP	.563 in. 14.3 mm	.312 in. 7.9 mm
1/2 Sched.160 Pipe	<b>SA 356-P8P4**</b>	15k psi 1000 bar	1/2 npt, 1/4 nptf	.840 in. 21.3 mm	.470 in. 11.9 mm
1/2 Sched.160 Pipe	<b>SA 356-P8P8</b>	15k psi 1000 bar	1/2 npt, 1/2 npt	.840 in. 21.3 mm	.470 in. 11.9 mm
3/4 Sched.160 Pipe	<b>SA 366-P12P12</b>	15k psi 1000 bar	3/4 npt, 3/4 npt	1.05 in. 26.7 mm	.610 in. 15.5 mm
3/4 MPTubing	<b>SA 577-M12M12</b>	20k psi 1400 bar	3/4 MP, 3/4 MP	.750 in. 19.1 mm	.438 in. 11.1 mm
3/4 MPTubing	<b>SA 577-M12P4</b>	20k psi 1400 bar	3/4 MP, 1/4 npt	.750 in. 19.1 mm	.438 in. 11.1 mm
3/4 MPTubing	<b>SA 577-G12P4**</b>	20k psi 1400 bar	3/4 G12, 1/4 npt	.750 in. 19.1 mm	.438 in. 11.1 mm
9/16 HPTubing	<b>SA 569-G9S6*</b>	40k psi 2800 bar	9/16 G9, 3/8-24	.563 in. 14.3 mm	.188 in. 4.8 mm

Notes: npt = National Pipe Thread MP = Cone & Thread Connection G12 tip for BJV 20k psi

\* Standard Lengths - 2, 3, 4, 8 in. (51, 76, 101, 203 mm) \*\* Standard Lengths - 3, 4, 6, 8, 10, 12 in. (76, 101, 152, 203, 254, 305 mm)

**EXTENSION NIPPLES**