

The Torus® - 3-D Tank Cleaning

The New 3-D Torus®

One Simple Tool for All Your Tank Cleaning Needs

Simplicity Efficiency Productivity

The **Torus®** is designed for multiple cleaning challenges. It operates under pressures from 2k - 22k psi by simply changing the manifold and inlet coupling. Plus, there are four different inlet couplings, and the three interchangeable manifolds are adjustable to handle flows from 17 - 80 gpm.

Comes with 2" and 8" Arms.
Longer extensions are available.
See pages 40 and 51.

Torus® Specs

Pressure	2k - 22k psi	138-1500 bar
Flow Capacity	17-80 gpm	64-303 lpm
Flow Rating	2.11 Cv	
Power	50-950 hp	37-708 kW
Cycle Time	4-24 minutes	
Inlet Options	3/4" or 1" npt or 3/4" or 1" MP	
Diameter	5.62 in.	143 mm
Weight	35 lbs	15.9 kg

NEW



- 2k-22k psi
- Simple to maintain
- Change manifold and coupling to meet different pressure and flow ratings
- Magnetic Speed Control



Magnetic Speed Control

The **Torus®** offers long lasting and durable magnetic speed control. Operators can easily adjust the magnetic rotation speed to adapt to different applications. The dial adjusts easily to decrease the speed for difficult applications and increase the speed for the easier applications. If the arms hit an obstruction the tool simply stops rotating and there are no broken gears to repair or replace.