

NIPPLES

- Three connection types available
- Stainless steel
- Glands and collars not included

LEFT HAND • MEDIUM PRESSURE TUBING (MP TUBE LH):


Available in 1/4 to 1". Used in standard medium pressure connections (using glands and collars) or with lance fittings (no glands and collars) or nozzles that have medium pressure left-handed female threads.

RIGHT HAND • MEDIUM PRESSURE TUBING (MP TUBE RH):


Used with lance fittings (no glands and collars) or nozzles that have medium pressure right-handed female threads. Available in 1/4 to 3/4 sizes.

LANCE CONNECTIONS:


Right-handed connections for use with nozzles and lance fittings. Available in 1/4, 3/8, and 9/16 sizes.



MP TUBE LH CONNECTION



MP TUBE RH CONNECTION



LANCE CONNECTION

PART NO. <i>Specify length in inches, in place of "XX"</i>	CONNECTION TYPES		MAX. WORKING PRESSURE		LENGTH	
	CONNECTION 1	CONNECTION 2	psi	bar	in	mm
SA 517-MP4LMP4L-XX	1/4 MP LH Male	1/4 MP LH Male	22,000	1,500	3-24	76-609
SA 517-MP4RMP4L-XX	1/4 MP RH Male	1/4 MP LH Male	22,000	1,500	3-24	76-609
SA 517-MP4RMP4R-XX	1/4 MP RH Male	1/4 MP RH Male	22,000	1,500	3-24	76-609
SA 537-MP6LMP6L-XX	3/8 MP LH Male	3/8 MP LH Male	22,000	1,500	3-24	76-609
SA 537-MP6RMP6L-XX	3/8 MP RH Male	3/8 MP LH Male	22,000	1,500	3-24	76-609
SA 537-MP6RMP6R-XX	3/8 MP RH Male	3/8 MP RH Male	22,000	1,500	3-24	76-609
SA 567-MP9LMP9L-XX	9/16 MP LH Male	9/16 MP LH Male	22,000	1,500	3-24	76-609
SA 567-MP9RMP9L-XX	9/16 MP RH Male	9/16 MP LH Male	22,000	1,500	3-24	76-609
SA 567-MP9RMP9R-XX	9/16 MP RH Male	9/16 MP RH Male	22,000	1,500	3-24	76-609
SA 577-MP12LMP12L-10.5	3/4 MP LH Male	3/4 MP LH Male	22,000	1,500	3-24	76-609
SA 577-MP12RMP12L-XX	3/4 MP RH Male	3/4 MP LH Male	22,000	1,500	3-24	76-609
SA 577-MP12RMP12R-XX	3/4 MP RH Male	3/4 MP RH Male	22,000	1,500	3-24	76-609
SA 577-G12P4-XX-0	3/4-16 RH Male O-Ring	1/4 NPT Female	22,000	1,500	3-24	76-609
SA 587-MP16LMP16L-XX	1" MP LH Male	1" MP LH Male	22,000	1,500	3-24	76-609
SA 587-MP16RMP16L-XX	1" MP RH Male	1" MP LH Male	22,000	1,500	3-24	76-609
SA 587-MP16RMP16R-XX	1" MP RH Male	1" MP RH Male	22,000	1,500	3-24	76-609